

Specifications

Model	8016HF	1025HF	1040HF	1060HF
Type of generator	Monobloc design (high frequency inverter generator, full bridge discrete IGBT)			
Power requirement (max.)	1.2 kVA	1.6 kVA	2.4 kVA	3.2 kVA
Adjustable kV (1kV steps)	40 - 80 kV	40 - 100 kV	40 - 100 kV	40 - 100 kV
mAs range	0.32 - 30 mAs (22 steps)	0.32 - 50 mAs (22 steps)	0.32 - 100 mAs (26 steps)	0.32 - 100 mAs (26 steps)
Maximum programmed mA output by kV level	10, 15, 16 mA	15, 20, 25 mA	20, 26, 30, 35, 40 mA	25, 30, 35, 40, 50, 60 mA
Focal spot of tube	1.0 x 1.0 mm	1.2 x 1.2 mm	1.2 x 1.2 mm	2.0 x 2.0 mm
Exposure time	0.02 - 2.5 sec			
Total filtration	2.5 mm Al (including collimator)			
Collimator light field	27 x 27 cm @ 66cm SID	35 x 35 cm @ 66 cm SID / 40 x 40 cm @ 75 cm SID		
Collimator lamp	Duration of 30 sec (controlled by both of hand switch and OP panel) Higher than 100lx (12/50W) light intensity			
OP & LED display	7 segment operation display for kV, mAs setting Ready, X-ray, Wait and Error (low voltage or overload) Buttons of Collimator lamp ON/OFF, Laser pointer ON/OFF, APR storage key and Display reverse.			
APR memory	8 memory standard and extendable to 16 combinations			
SID measurement	Dual laser pointer & tape measuring			
Protection	Overload protection of high frequency inverter and X-ray tube			
Line voltage (required)	110 ~ 130 VAC 50/60 Hz single phase 20A or 200 ~ 260 VAC 50/60 Hz single phase 16A			200-260 VAC 50/60 Hz single phase 16A
Weight (without accessories)	6.4 kg	9.9 kg	12.5 kg	13.5 kg
Size (L x W x H) mm	280 x 140 x 150	344 X 178 X 175	344 x 191 x 188	344 x 191 x 210
Accessories	Hand carry box (Aluminum case) with a shoulder strap, AC PWR cable (6m long), Extra fuses and a halogen lamp, a Hand switch and a user manual			

Specifications are subjects to change without prior notice.



EcoRay Co.,LTD.

B-904, Woolim Lions Valley, 371-28, Gasan-Dong, Geumcheon Gu, Seoul, Korea 153-786  
Tel) +82 2 2026 3600 Fax) +82 2 2026 3609  
email to [sales@acomaxray.com](mailto:sales@acomaxray.com) / [sales@ecoray.kr](mailto:sales@ecoray.kr)  
Visit us at [www.acomaxray.com](http://www.acomaxray.com) / [www.ecoray.kr](http://www.ecoray.kr)

Power in compact bodies  
**ORANGE Series**

Durable & advanced technology for  
**portable X-ray units**  
(High Frequency Inverter Generators)



X-ray with Design & Technology





Power in compact bodies

## ORANGE Series

Durable & advanced technology for  
portable X-ray units (High Frequency Inverter Generators)

Orange portable X-ray units are applicable to medical, veterinary and industrial purpose and it is light, compact and powerful to be handled or carried from one place to another.

Ecoray's high frequency inverter technology is heading to the destination of more premium, more durable and more comfortable imaging solution. These units and applications are helpful to not only first-aid examination but main imaging solutions in your X-ray room.

Orange series with Robust design is the best selection for whom they look for the units with durability and performance.



### ORANGE 8016HF

**Better choice for your Equine examinations!**  
(Hold it in your one hand only)

- Power with quality (80 kV/16mA output)
- Wider range of kV (40 - 80 kV) in 1 kV steps
- Easy access to DR systems
- Flashing idea to Collimator Slot - easy and smooth enough
- Durable design with reliable radiation output



### ORANGE 1040HF

**The best seller in the line.**  
**Most popular range that covers all..!!!**

- Outstanding & Stable imaging capability
- Durable housing and design
- Compact size but powerful output (100 kV/ 40mA)
- Ergonomic & Soft OP panel layout
- Right selection for small animal and equine stifles radiography

### ORANGE 1025HF

**Upgraded power  
by innovative concept**

- Power in a tiny body (100 kV/25mA)
- Strong 100 kV output
- Compact & light weight with higher mA range up to 25mA
- Wide range of application : From equine lower limb to small animal surgery
- Reliable performance from Robust body



### ORANGE 1060HF

**Premium value  
with superior output**

- Extraordinary X-ray output. 60mA Strength
- Small enough + Strong enough
- Powerful output (100 kV/60 mA max.) from compact size - Similar with 1040HF
- Suitable for your small animal examinations
- Convenient handling for advanced image quality

